

L-SERIES

WATER-COOLED* TWO-STAGE

60 HZ

Dimensions and Specifications

Typical, do not use for construction. (Drawings are provided with order acknowledgement.)

Model	Motor HP	Max. Pressure PSID	Free Air** Delivery CFM	Length In.	Width In.	Height In.	Net Weight Lbs.
KNW00-A/L	20	100	73	85	36	61	2190
KNW00-B/L	25	100	93	85	36	61	2320
KNW00-C/L	30	100	125	85	36	61	2410
KNW00-D/L	40	100	165	85	36	61	2540
KNW0-A/L	40	100	175	70	49	54	3670
KNW0-B/L	50	100	225	70	49	54	3740
KNW0-C/L	60	100	294	70	49	54	3800
KNW0-D/L	75	110	333	70	49	54	3910
KNW0-E/L	100	135	400	70	49	54	4100
KNW1-A/L	100	125	417	100	63	60	5620
KNW1-B/L	100	110	508	100	63	60	5970
KNW1-C/L	100	100	537	100	63	60	5970
KNW1-D/L	125	110	622	100	63	60	6220
KNW1-E/L	125	110	657	100	63	60	6220
KNW1-F/L	150	115	732	100	63	60	6460
KNW1-G/L	200	125	815	100	63	60	6040
KNW2-A/L	200	125	915	124	75	72	10000
KNW2-B/L	200	100	1102	124	75	72	10200
KNW2-C/L	250	110	1316	124	75	72	11000
KNW2-D/L	300	110	1559	124	75	72	11600
KNW3-A/L	350	110	1782	139	82	92	12050
KNW3-B/L	400	115	1951	139	82	92	12040
KNW3-C/L	450	115	2170	139	82	92	12840
KNW3-D/L	500	115	2389	139	82	92	13150

For air cooled requirements, refer to Bulletin KNWA/L & KNWA/H

